Xerox® WorkCentre™ 5945/5955
Multifunction Printer

The WorkCentre 5945/5955 Multifunction Printer is built on Xerox® ConnectKey® Technology. For more information, go to **www.connectkey.com**.

WorkCentre 5945 shown with Office Finisher

WorkCentre 5955 shown with Office Finisher with Booklet Maker

System Specifications	WorkCentre 5945	WorkCentre 5955
Simplex Speed A4 / 8.5 x 11 in. (LEF) A4 to B4 / 8.5 x 13 to 8.5 x 14 in. (SEF) A3 / 11 x 17 in. (A3 SEF) (Bypass Tray will reduce speed by 10 to 20%)	45 ppm 36 ppm 31 ppm	55 ppm 36 ppm 31 ppm
Auto Duplex Speed A4 / 8.5 x 11 in. (LEF) A3 / 11 x 17 in. (SEF)	Up to 45 ipm / 2-sided 22.5 sheets per minute Up to 31 ipm / 2-sided 15.5 sheets per minute	Up to 55 ipm / 2-sided 27.5 sheets per minute Up to 31 ipm / 2-sided 15.5 sheets per minute
Monthly Duty Cycle[1]	Up to 175,000 pages	Up to 200,000 pages
Recommended Average Monthly Print Volume[2]	Up to 20,000 pages	
Hard Drive / Processor / Memory	Minimum 250 GB / 1 GHz Dual-core / 2 GB system	
Connectivity	10/100/1000Base-T Ethernet, High-Speed USB 2.0 direct print, Optional Wi-Fi (with Xerox® USB Wireless Adapter)	
Controller Features	Unified Address Book, Remote Control Panel, Online Support (accessed from the user interface and print driver), Configuration Cloning	
Copy and Print		
Copy and Print Resolution	**Copy**: Up to 600 x 600 dpi; **Print**: Up to 1200 x 1200 dpi, 256 shades of grey	
First-copy-out Time	As fast as 3.7 seconds from the Platen / 7.6 seconds from the Automatic Document Feeder	
Page Description Languages	Adobe® PostScript® 3™, PDF, PCL® 5c / PCL 6, XML Paper Specification (XPS®) (Optional)	
Print Features	Print from USB, Earth Smart Driver Settings, Job Identification, Booklet Creation, Store and Recall Driver Settings, Bi-directional Status, Scaling, Job Monitoring	
Mobile Printing	Apple® AirPrint, Xerox® PrintBack, Xerox® Mobile Print (Optional), Xerox® Mobile Print Cloud® (Optional), Mopria™ certified, Xerox® Print Service (plug-in for Android™)	
Scan		
Standard	**Destinations:** Scan to Mailbox; Scan to USB, Scan to Email, Scan to Network; **File Formats:** PDF, PDF/A, XPS, JPEG, TIFF; **Convenience Features:** Scan to Home, Single Touch Scan, Searchable PDF, Single/Multi-Page PDF / XPS / TIFF, Encrypted / Password Protected PDF, Linearised PDF / PDF/A	
Optional	**Software Packages:** ConnectKey® for SharePoint®, ConnectKey® for DocuShare®, ConnectKey® Share to Cloud, Xerox® Scan to PC Desktop® Professional, other solutions available through various Xerox Alliance Partners	
Fax		
Standard Features	Internet Fax, Fax Build Job, Network Server Fax Enablement	
Optional Features	One-line and two-line options, includes LAN Fax, Fax Forward to Email or SMB, Walk-up Fax	
Security		
Standard Features	McAfee® Embedded, McAfee ePolicy (ePO) Compatible, HDD Overwrite, 256-bit Encryption (FIPS 140-2 compliant), Common Criteria Certification (ISO 15408) (undergoing evaluation), Secure Print, Secure Fax, Secure Scan, Secure Email, Cisco® TrustSec Identity Services Engine (ISE) Integration, Network Authentication, SSL, SNMPv3, Audit Log, Access Controls, User Permissions	
Optional Features	McAfee Integrity Control, Xerox Secure Access Unified ID System®, Smart Card Enablement Kit (CAC/PIV/.NET)	
Accounting		
Standard Features	Xerox® Standard Accounting (Copy, Print, Scan, Fax, Email), Network Accounting Enablement	
Optional Features	Equitrac Express®, Equitrac Office®, Equitrac Professional®, YSoft® SafeQ®, other network accounting solutions available through various Xerox® Business Innovation Partners	

Xerox® WorkCentre™ 5945/5955

Device Specifications	
Control Panel Languages	US English, International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian or Romanian, Catalan
Accessories	
Optional	Envelope Tray Kit (replaces Tray 2) Office Finisher Office Finisher with Booklet Maker Hole Punch for Office Finisher Convenience Stapler (includes Work Surface) Smart Card Enablement Kit Xerox Secure Access Unified ID System® (with USB Card Reader) Walk up Fax (One- or Two-line options, includes LAN Fax) ScanFlowStore® Xerox® USB Wireless Adapter McAfee® Integrity Control Enablement Kit XPS Print Option Kit
Foreign Device Interface (FDI) (Optional)	Also known as Auxiliary Access Device, this is an interface to third party access control devices, such as coin machines and card readers.
Electrical Requirements	
North America	Voltage : 110-127 VAC +/- 10 % Frequency: 50/60 Hz +/- 5 %, 15 A
Europe	Voltage : 220-240 VAC +/- 10 % Frequency: 50/60 Hz +/- 5 %, 10 A

Power Consumption	WorkCentre 5945	WorkCentre 5955
Running (Average) Base Unit with Offset Catch Tray: Base Unit with Office Finisher: Base Unit with Office Finisher with Booklet Maker:	1,150 watts 1,230 watts 1,230 watts	1,250 watts 1,330 watts 1,330 watts
Standby Mode Base Unit with Offset Catch Tray: Base Unit with Office Finisher: Base Unit with Office Finisher with Booklet Maker:	45 watts 55 watts 55 watts	45 watts 55 watts 55 watts
Sleep mode	3 watts	
Ready to Scan and Print (from Power On)	As fast as 230 seconds (3 minutes, 50 seconds)	
Recovery from Low Power	As fast as 4 seconds	
Recovery from Sleep	As fast as 28 seconds	
Operating Environment		
Required Temperature Range	10° to 32° C / 50° to 90° F	
Required Relative Humidity	15 % to 85 %	
Sound Power Levels	Operating 7.1 B(A), Standby: 5.0 B(A)	
Sound Pressure Levels	Operating: 56 dB(A), Standby: 35 dB(A)	

Dimensions and Weight	Width	Depth	Height	Weight
Base Configuration with Internal Tray	850 mm / 33.5 in.	665 mm / 26.2 in.	1,150 mm / 45.3 in.	113 kg / 249 lbs.
With Office Finisher	1,470 mm / 57.9 in.	665 mm / 26.2 in.	1,150 mm / 45.3 in.	142.5 kg / 314.5 lbs.
With Office Finisher with Booklet Maker	1,530 mm / 60.2 in.	665 mm / 26.2 in.	1,150 mm / 45.3 in.	158.5 kg / 349.5 lbs.
Work Surface (does not add to overall width with Bypass Tray open)	285 mm / 11.2 in.	–	–	–

Xerox® WorkCentre™ 5945/5955

Certifications	
	FCC Class A Compliant (US), ICES Class A Compliant (Canada) CSA Listed (UL 60950-1, Second Edition) CB Certified (IEC 60950-1, Second Edition) ENERGY STAR® GOST NOM Blue Angel ECOLOGO® CE Marked Common Criteria (IEEE 2600.2 standard) (undergoing evaluation) EPEAT (United States) GS Mark Citrix® Certified WHQL MEDITECH Cerner To view the latest list of certifications, go to **www.xerox.com/OfficeCertifications**.

Paper Handling

Single-pass Automatic Document Feeder

Capacity[3]	200 sheets
Speed (black and white and colour)	Up to 105 images per minute (ipm) (simplex) Up to 200 ipm (duplex) black and white, up to 160 ipm (duplex) colour
Paper Sizes Sensed	125 x 138 mm to 297 x 432 mm / 4.9 x 5.4 in. to 11.7 x 17 in.
Weights	50 gsm to 160 gsm / 13 lb. bond to 43 lb. bond

Bypass Tray

Capacity[3]	100 sheets
Sizes	Custom sizes: A6 to A3 / 4.25 x 5.5 in. to 11 x 17 in.
Weights	60 to 216 gsm / 16 lb. bond to 80 lb. cover
Types	Bond Carbonless Card Stock Envelopes Hole punched Index Labels Letterhead Plain Preprinted Recycled

Trays 1 and 2

Capacity[3]	500 sheets each
Sizes	Custom Sizes from A5 to A3 / 5.5 x 8.5 in. LEF to 11 x 17 in. SEF
Weights	60 to 200 gsm / 16 lb. bond to 53 lb. bond
Types	Bond Card Stock Glossy Hole punched Index Labels Letterhead Lightweight Card Stock Plain Preprinted Recycled Transparencies (Tray 2 only)

High Capacity Tandem Tray

Capacity[3]	Tray 3: 1,600 sheets Tray 4: 2,000 sheets
Sizes	Standard Sizes: A4 / 8.5 x 11 in. LEF
Weights	60 to 216 gsm / 16 lb. bond to 53 lb. bond

Xerox® WorkCentre™ 5945/5955

Types	Bond Card Stock Glossy Hole punched Index Letterhead Lightweight Card Stock Plain Preprinted Recycled
Envelope Kit (Replaces Tray 2)	
Capacity³	Up to 50 envelopes
Sizes	#10 Commercial (9.25 x 4.125 in.), DL, C5
Weights	75 to 90 gsm / 20 lb. bond to 24 lb. bond
Total Capacity	
Device Total Capacity³	4,700 sheets
Finishing	
Centre Offsetting Tray	
Capacity	Up to 400 sheets of 80 gsm / 20 lb. bond
Office Finisher (Optional)	
Top Tray Capacity **Stacking Tray Capacity**	250 sheets unstapled of 80 gsm 2,000 sheets unstapled of 80 gsm or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in. / A4)
Top Tray Sizes **Stacking Tray Sizes**	A6 to A3 / 4.25 x 5.85 in. to 11 x 17 in. A5 to A3 / 5.5 x 8.5 in. to 11 x 17 in.
Weights	60 to 216 gsm / 16 lb. bond to 58 lb. bond
Multiposition Stapling	50 sheets of 80 gsm / 20 lb. bond
Hole Punch (Optional) North America: Europe:	2-3 Hole Punch 2-4 Hole Punch
Office Finisher with Booklet Maker (Optional)	
Top Tray Capacity **Stacking Tray Capacity**	250 sheets unstapled of 80 gsm 2,000 sheets unstapled of 80 gsm or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in. / A4)
Top Tray Sizes **Stacking Tray Sizes**	A6 to A3 / 4.25 x 5.85 in. to 11 x 17 in. A5 to A3 / 5.5 x 8.5 in. to 11 x 17 in.
Weights	60 to 216 gsm / 16 lb. bond to 58 lb. bond
Multiposition Stapling	50 sheets of 80 gsm / 20 lb. bond
Hole Punch (Optional) North America: Europe:	2-3 Hole Punch 2-4 Hole Punch
Booklet Making Capacity³	40 booklets (2-15 sheets per booklet – 80 gsm / 20 lb. or less)
Booklet Making Sizes	A4 / 8.5 x 11 in. (SEF) B4 / 8.5 x 14 in. (SEF) A3 / 11 x 17 in. (SEF)
Saddle-stitch Stapling	2-15 sheets / 8 – 60 page booklet 60 to 90 gsm / 16 lb. bond to 24 lb. bond
Folding	1-15 sheets / unstapled
Convenience Stapler (Optional – Includes Work Surface)	
Capacity³	50-sheet stapling 5,000 staples Requires a separate power outlet
Copy	
First-copy-out Time	As fast as 3.7 seconds from the Platen / 7.6 seconds from the Automatic Document Feeder
Sides (input:output)	1-1, 1-2, 2-2, 2-1
Quantity	1 to 9,999
Resolution (max.)	Scan: Up to 600 x 600 dpi; Print: Up to 1200 x 1200 dpi, 256 shades of grey
Reduction / Enlargement	Variable zoom from 25 % to 400 % in 1 % increments
Concurrency	Programme-ahead to allow job to be initiated while initial job is processed (Copy, Print, Fax and Scan)

Xerox® WorkCentre™ 5945/5955

Copy Features	Annotation and Bates™ stamping (with colour capability and font size adjustment) Authentication for Services Auto Paper Select Auto Reduction & Enlargement to fit selected paper size Auto Tray Switching Automatic 2-sided / Duplex Booklet Creation Build Job: (Enables page-level programming and also lets you proof each section or delete last section as the job is built) Collation Covers (Front only, front and back, back only, printed inside and out: Blank or Printed) Dividers (blank) Edge Erase Features Help (Intuitive text and graphic descriptions) ID Card Copy Image Quality Adjustments Image Shift (with Auto Centre option) Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settings Stapling Transparencies
Xerox® Copier Assistant®	Xerox® Copier Assistant® (XCA) Software provides a PC-based alternative to the user interface touch screen. Used in conjunction with a customer-supplied PC attached via the USB port, this software supports text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features. Section 508 compliant. For more information or to download Xerox® Copier Assistant for free, visit **www.xerox.com**

Print

First-print-out Time	As fast as 7 seconds
Print Resolution	Up to 1200 x 1200 dpi, 256 shades of grey
Print Features	Application Defaults Banner Sheet Enable / Disable Bi-directional Status Cover Selection Delay Print (specific time) User Permissions Image Options (Toner Saver, Resolution (Standard, Enhanced, High) Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) LAN Fax (requires optional Fax Kit) Layout / Watermark (N-up (up to 16 pages per sheet), Multi-up, Booklet layout / finishing, Fit to new paper size) Overlays Paper Selection by Attribute Sample Set Saved Job Secure Print with Timed Deletion Special Pages (exception page programming: covers, inserts, exception pages) Store and Recall Driver Settings Sustainability Features (Xerox® Earth Smart Settings, Duplex, N-up, Turn-off Banner and Print ID, Smart Sample Set, Hold All Jobs)
Print from USB	Allows walk-up printing from Type A USB port on front panel Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, PS, XPS[4], PCL
Operating Systems	Microsoft® Windows® XP SP3 (32- and 64-bit) Windows Server 2003 (32- and 64-bit) Windows Server 2008 and R2 (32- and 64-bit) Windows Server 2012 and R2 Windows Vista SP2 (32- and 64-bit) Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Windows 8.1 (32- and 64-bit) Mac OS 10.7, 10.8, 10.9 Linux® Redhat® Fedora® Core 19 x86 Ubuntu® 13.10 x64 openSUSE® 13.1 x64
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6,WSD NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway) AppleTalk®: EtherTalk® Microsoft Windows Networking over IP Apple® Bonjour® IPv6 Secure FTP Most protocols not in use can be disabled
Administrative Protocols	DHCP, BOOTP, SNMP, WINS, SLP® v2, HTTP, HTTPS, DHCP Autonet, SSL, NTP, DNS, SSDP

Xerox® WorkCentre™ 5945/5955

Fonts	PCL: 93 scalable fonts, line printer and bitmap font (including Cyrillic font support) PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts
Xerox® Mobile Express Driver®	Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox® devices in every new location. Plug into a new network, and Xerox® Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favourite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.
Xerox® Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Xerox Secure Access Unified ID System®, Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.
Print Solutions	
Xerox® Mobile Print Cloud (Optional)	Xerox® Mobile Print Cloud addresses the needs of businesses with a mobile workforce and puts you ahead of the evolving mobile print need, but without burdening staff, budget or infrastructure. Getting started takes only a few minutes via the cloud. Print from any mobile device to nearly any brand of printer. Accurate printing with true Microsoft® Office® rendering and more. Print what you need, when, where and how you need it.
Xerox® Mobile Print Solution (Optional)	Xerox® Mobile Print Solution is an ideal choice for sites that have additional requirements for control and security with an onsite server. Xerox® Mobile Print Solution allows users to print from most mobile devices to nearly any brand of printer or MFP without drivers or added complexity. Simply enter a release code (PIN) at the device and get accurate printing with true Microsoft Office rendering and more to use with your server for private, onsite deployment.
Unified Address Book	
Features	Services supported: Fax, Internet Fax, Email, Scan to Maximum contacts: 5,000 Contacts: Supports 1 or more destinations Favourites for quick access of fax numbers, emails, etc.
Scan	
Concurrency	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs (priority is for return of scanned originals and printing concurrent jobs)
Input Speed	Scan at up to 160 ipm colour scanning and 200 ipm black and white scanning – A4 / 8.5 x 11 in. (LEF)
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black and white), 8-bit (greyscale), 24-bit (colour)
Maximum Scan Area	A3 / 11 x 17 in.
Scan Template Management	Support 250 scan templates Create Xerox® CentreWare® IS scan templates and share via device cloning to other MFPs Confirmation sheet options
Network Protocols	sFTP, FTP, SMB, NetWare, HTTP, HTTPS
File Compression	Colour TIFF (TIFF 6.0 or TTN2 with JPEG, LZW) Black and white TIFF (G3MH, G4 MMR compression – single or multiple pages) Searchable PDF and PDF/A (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for Black and white and within MRC)) Linearised PDF / PDF/A
Document Management Fields (Meta Data)	Features only available in Network Scan to File Templates: • 1 to 6 user programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata field consists of field name, default value and other configurations • Customised fields viewed on user interface for variable data input
Scan Features	Mixed Size Originals Scan Build Job Compression Quality / File Size Control Original Type (Photo and Text, Photo, Text, Map, Newspaper / Magazine) Auto Background and Shadow Suppression Size for Size (for mixed size originals) TWAIN Support / WIA Support Bound Originals Edge Erase Reduction / Enlargement Single Touch Scan buttons (up to 10)
Scan to Email (Standard)	
Scan Features	• Email signatures (6 lines each of 128 character max), email message body (user configurable), email CWIS confirmation sheet options • Scan to Email S/MIME Encryption • Email signing (requires Smart Card option) • Auto send to self
Directory Access	Address list via LDAP (Windows Archive Directory, Exchange, Notes, Domino) Downloaded address list (comma-separated file format) Utilizes the Unified Address Book
Scan to… (Standard)	
Features	Scan to USB Scan to Network Folder (uses Unified Address Book entries)

Xerox® WorkCentre™ 5945/5955

Network Scanning – Software Solutions	
Xerox® Scan to PC Desktop® Professional (Optional)	A desktop offering that provides advanced document imaging, archiving, editing and organisation tools: • PaperPort Professional image viewing and file management software – Complete PDF functionality – Secure PDF workflow of all scanning applications • OmniPage Pro Office (for desktop/client installation) – Professional OCR software for digital archiving and document conversion • Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox® WorkCentre to individual desktops. Also includes email inbox polling capability
Xerox® ConnectKey® for SharePoint® (Optional)	Xerox® ConnectKey for SharePoint simplifies and streamlines the way you scan, capture and store your paper-based documents. Using your Xerox® MFP, you can route documents directly into the precise document repository folder, just like you would from your PC. At the MFP, you can browse to the folder, name the document, and add any key indexing information before you scan. With the flexibility to capture and route to SharePoint as well as Windows folders, ConnectKey Technology is the right solution for any office that needs to archive and share paper-based documents.
Xerox® ConnectKey Share to Cloud (Optional)	Xerox® ConnectKey Share to Cloud provides organisations with powerful, easy and secure document scanning capabilities that connect your Xerox® MFP to popular cloud services and email, such as Google Docs™, SalesForce.com, Office 365 and Dropbox™ and gives employees anytime, anywhere access to their most important documents using mobile devices.
Xerox® ConnectKey® for DocuShare® (Optional)	Xerox® ConnectKey for DocuShare, a one-step scan-to-workflow solution, simplifies the process of incorporating hard copy content into enterprise document flows. Users can easily scan documents directly into a DocuShare collection or Windows folder via a multifunction printer (MFP).

Security	
Features	• Expanded Authentication – Network authentication to access device and/or device services via- Kerberos (UNIX / Windows Server 2003 / Windows Server 2008), SMB (Windows 2000 / Windows Server 2003 / Windows Server 2008), NDS, LDAP – Xerox® Secure Access – Local Authentication (internal database) – Smart Card authentication -144k CAC / PIV Card Support (2048 bit certificate key) / .NET • Secure Data – Digitally signed PDF (when using Smart Card authentication) – Encrypted Scan to Email – Encrypted / Password Protected PDF (Email and Network Scan Templates only) – Secure Print (up to 10 digit PIN or Network Authentication) – Immediate Image Overwrite – On Demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk – FIPS 140-2 256 bit Hard Disk Encryption • Expanded Authorisation – SA access based on network credentials – Authorisation per user per service – User Permissions required to access Print and Print Features (e.g. colour access, or time restrictions) reflects in the print driver • Secure Network Access • IP Filter, IPsec, IPv6, SSL v3.0, SNMPv3, HTTPS, 802.1X, Cisco® TrustSec Identity Services Engine integration (optional), Device Security – McAfee® Embedded Security, Port disablement including USB ports, Audit Log, Hide Print Job Names, , McAfee Integrity Control (optional) • Common Criteria Certification ISO 15408 (undergoing evaluation)
Xerox Secure Access Unified ID System® (Optional)	Xerox Secure Access Unified ID System integrates your Xerox® multifunction printers with your existing employee/student ID PIN or badge providing a flexible and convenient authentication system. Allow your staff, employees or students to send documents to a centralised print server. Then, at any multifunction printer on the network, they'll simply log in with a swipe of their magnetic or proximity ID card or their PIN to securely print their job. For more information, go to **www.office.xerox.com/software-solutions**

Fax	

Network Server Fax Features	
Compatibility	ITY (CCITT) group 3 Various Xerox® Business Innovation Partner Solutions
Maximum Scan Area	A3 / 11 x 17 in.
Fax Send Features	One- or two-sided scanning (up to A3 / 11 x 17 in.) Add to send list (50 numbers maximum) Build Job, Favourites, Delay send (specific time) Original type (photo, text or photo and text)
Fax Print Features	One- or two-sided printing, staple, Secure Print
Transmission Resolution	Superfine: 400 x 200 dpi (Scan at 600 x 600 dpi) Fine: 200 x 200 dpi Standard: 200 x 100 dpi

Internet Fax Features	
Capability	Direct print-ready document transmission to remote Internet Fax machines or email clients (SMTP) Reception and automatic printout of documents sent via email from remote Internet Fax machines or email clients
Address Directory Access	Send: Multi-page TIFF, PDF, PDF/A Receive: TIFF, MTIFF, PDF, PDF/A, PS, text, PCL, PRN, JPEG
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black and white)
Network Protocols	SMTP (send), POP3 (receive)
Compliance	ITU-T T.37 compliant

Walk-up Fax Features (Optional (Customer-installable) – 1 and 2 lines)	
Compatibility	ITU (CCITT) Group 3
Speed / Modems	One or Two V.34 modems: 33,600 bps. Less than 4 seconds per page transmission time ATA analogue terminal adapter utilising T38 (optional)

Xerox® WorkCentre™ 5945/5955

Compression / Speed	MH/G3, MMR/SG3
Resolution	**Walkup Send:** Standard: 200 x 100 dpi Fine: 200 x 200 dpi Superfine: 600 x 600 dpi **Receive:** Accepts all sizes
Fax Send Features	LAN Fax (fax from print driver) Auto fax transmission reduction Page-by-page job status at the machine Delay start, Build Job, Favourites Automatic memory resend Automatic cover sheets PSTN Fax Device Address Book (up to 1,000 contacts)
Fax Receive Features	One- or two-sided printing Stapled or unstapled Receive print mode – Manual (size, margin, stock, header) / Auto Output tray selection Up to 200 password protected mailboxes Secure receive Receive timestamp Auto answer delay
Fax Forward	Forward to Email or SMB Location Fax forward on receive only
Fax Reports	Activity, Dial directory, Group directory, Transmission confirmation, Pending fax, Options report, On demand overwrite report, Mailbox report, Broadcast report
Auto Dialing	Speed Dials: 5,000 total (one- or two-line options) Group Dials: Up to 200 groups with up to 400 recipients per group (one- or two-line options) Auto Redial: Up to 14 attempts (per country requirements) • 1 to 25 minute intervals • Batch send (up to memory capacity)
Device Management	
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213), Host Resources MIB RFC 2790, Printer MIB RFC 1759 v.2
Xerox® CentreWare® Web	A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system: • Works with any SNMP-managed printer from any manufacturer. • Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. • Requires Windows XP, Vista or Windows 7 and Internet Explorer 6.0 and higher. • CentreWare Integration available for Tivoli® NetView®, Unicentre TNG®, Microsoft Management Console (MMC), HP® OpenView®
Novell NDPS/NEPS	Server gateway application: centralised management tool.
Xerox® Device Manager	Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: • Device monitoring and troubleshooting • Extensive reporting and discovery of new devices • Usage collection, chargeback and billing capabilities
Xerox® Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Programme, provides seamless connectivity between SAP systems and your Xerox® printers and MFPs. And as an SAP customer you benefit from having SAP-certified Xerox® device types available right from SAP's online delivery model. SAP-certified device types for Xerox® printers and MFPs are available to download. **www.office.xerox.com/software-solutions**
Xerox® SAP R/3 Intelligent Barcode Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Centre Barcode Fonts. Information available at **www.office.xerox.com/software-solutions**
Xerox® Barcode Pro PS (optional)	Enables intelligent PostScript printing on Xerox® multifunction systems by storing Xerox software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP client or mainframe) that supports PostScript printing. Information available at **www.office.xerox.com/software-solutions**
CentreWare Internet Services – Integrated Web Pages Provided by the Device	
Device Status	Web server embedded in Network Controller: • Tray status/contents • Consumables status • Alerts Remote Control Panel
Job Submission	Print ready files: PS, PCL, TIFF, PDF, JPG, XPS[4], TXT, PRN Output feature selection (2-sided, output colour, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)
Device Administration	Allows simple, remote installation setting of configuration options and management of the device

Browsers	Internet Explorer 7.x, 8.x, 9.x Safari 5.x Mozilla Firefox 4.x, 5.x, 6.x, 7.x, 8.x, 9.x, 10.x, 11.x Opera 11.x Chrome 12
Support	Install print / scan drivers and online support available via web page
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish or Russian, Simplified Chinese, Korean, Japanese

Remote Print Services

Automatic Meter Reading (AMR) (May not be available in all regions)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
Automatic Supplies Replenishment (ASR) (May not be available in all regions)	Automatically orders supplies for Xerox output devices based on actual usage, eliminating the need to manually manage supplies inventory (may not be available in all countries).

Accounting

Xerox® Standard Accounting (Standard)

Tracking	Copy, Print, Fax, Scan and Email usage
Accounting	Up to 2,497 User accounts (User ID) Up to 500 General accounts (Client) Up to 498 Group accounts (Department)
Features	• Administrator can manage the feature via the Web User Interface or device control panel in tools • Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV file

Accounting Options – Network Accounting – Third Party Enablement

	• Enhanced network accounting with up to the minute data on how the system is being used • Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax • Numerous solutions are available through Xerox Business Innovation Partners. For details visit **www.xerox.com** • Security enhancements with the addition of HTTPS protocol support • WorkCentre requests account authentication from third party server enabling larger databases of users and accounts • Accept Authentication Login at control panel and pass to third party Networking Account Interface with third party accounting terminal for accounting user interface

Supplies	Description	Quantity	Part Number
Toner Cartridge	Includes 2 Toner Cartridges	88,000 pages[5] (44,000 pages each)[5]	006R01606
	Office Finisher with Booklet Maker – saddle-stitch stapling	2,000 per cartridge (8,000 staples)	108R01158
	Convenience Stapler – Complete Cartridge – Refill Cartridge	5,000 per cartridge 5,000 per cartridge (15,000 staples)	008R12964 008R12941

Smart Kits®

Fuser Module	North America: Europe:	350,000[5] 350,000[5]	109R00847 109R00848
Print Cartridge	Includes xerographic drums, developer module, including dual auger ring, toner despense, toner concentration sensor, development roll, trim bar and developer material	200,000[5]	013R00669

[1] Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.
[2] Expected regular monthly throughput
[3] Paper capacities are based on 75 gsm / 20 lb. stock; capacities will vary with different weight stocks.
[4] XPS option is required to print XPS files.
[5] Average standard pages. Declared Yield in accordance with ISO/IEC 19752. Yield will vary based on image, area cover and print mode.

Return spent imaging supplies through the Xerox® Green World Alliance collection/reuse/recycling programme. For more information, visit **www.xerox.com/about-xerox/recycling**.

For more information, visit us at **www.xerox.com/office**.